

# PRODUCT DATASHEET LED VALUE CLAS A 100 13 W/4000 K E27

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

#### **Product benefits**

- Very low energy consumption
- Can be easily fitted instead of ordinary light bulbs

#### **Product features**

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering ( $R_a \ge 80$ ) and color stability throughout the life of the lamp



#### **TECHNICAL DATA**

#### **Electrical data**

Nominal wattage	13 W
Construction wattage	13.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	100 W
Nominal current	100 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp no. on circuit break. 10 A (B)	80
Max. lamp no. on circuit break. 16 A (B)	128
Total harmonic distortion	< 100 %
Power factor $\lambda$	> 0.50

# Photometrical data

Luminous flux	1521 lm
Nominal useful luminous flux 90°	1521 lm
Luminous efficacy	117 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	200 °
Warm-up time (60 %)	0.50 s
Starting time	< 0.5 s
Rated beam angle (half peak value)	200.00 °

# **Dimensions & Weight**

Overall length	118.00 mm
Diameter	60.00 mm

Maximum diameter	60 mm
Product weight	43.00 g

## Temperatures & operating conditions

#### Lifespan

Lifespan	15000 h
Number of switching cycles	100000
Lumen maintenance at end of serv	0.70
Rated lamp survival factor at 6,000	≥ 0.90

#### Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

#### Capabilities

Dimmable	No
----------	----

#### **Certificates & Standards**

Energy efficiency class	F <sup>1</sup> )
Energy consumption	13.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RGO

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

#### **Country-specific categorizations**

Order reference	VALUECLA100 13W

# LOGISTICAL DATA


-20...+80 °C



## Energy labelling regulation data acc EU 2019/2015

Correlated colour temperature typeSINGLE_VALUELength118.00 mmHeight60.00 mmWidth60.00 mm	
Height 60.00 mm	
Width 60.00 mm	
00.00 mm	
R9 Colour rendering index 0.00	
EPREL ID 1403212,523300	
Model number AC31142,AC24696	

# DOWNLOAD DATA



#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075476097	Folding box 3	182 mm x 62 mm x 122 mm	167.00 g	1.38 dm <sup>3</sup>
4058075476103	Shipping box 30	379 mm x 325 mm x 148 mm	2208.00 g	18.23 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.