

PRODUCT DATASHEET

BASE CLAS A 60 FR 8.5 W/2700K E27

LED BASE CLASSIC A | LED lamps, classic bulb shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

PRODUCT BENEFITS

- Very low energy consumption
- Shockproof and vibration-proof thanks to LED technology
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

PRODUCT FEATURES

- Professional LED lamps for line voltage
- Not dimmable
- Base: E27, B22d
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Rated wattage	8.50 W
Nominal wattage	8.50 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	109
Max. lamp no. on circuit break. 16 A (B)	175
Operating frequency	50...60 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	60 W


Photometrical data

Rated luminous flux	806 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	806 lm
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdcn
Nominal luminous flux	806 lm
Rated color temperature	2700 K
Color rendering index Ra	≥ 80

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	107.0 mm
----------------	----------

Diameter	60.0 mm
Outer bulb	A60
Length	107.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	100 °C

Lifespan

Nominal lamp life time	10000 h
Rated lamp life time	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E27
Mercury-free	Yes
Design / version	Frosted
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Mercury content	0.0 mg

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Energy efficiency class	A+
Energy consumption	9 kWh/1000h

Country-specific categorizations

ILCOS	DRAA/F-9/827-220-240-E27-60
Order reference	BASECLA60 8,5W/

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899955493	Folding carton box 3	61 mm x 153 mm x 143 mm	103.00 g	1.33 dm ³

4052899955523	Shipping carton box 30	315 mm x 313 mm x 122 mm	1442.00 g	12.03 dm ³
4052899972476	Blister 3	62 mm x 140 mm x 185 mm	118.00 g	1.61 dm ³
4052899972483	Shipping carton box 18	377 mm x 148 mm x 201 mm	861.00 g	11.21 dm ³
4058075090484	Folding carton box 5	61 mm x 242 mm x 112 mm	178.00 g	1.65 dm ³
4058075090491	Shipping carton box 50	495 mm x 318 mm x 126 mm	2427.00 g	19.83 dm ³
4058075152656	Folding carton box 2	61 mm x 116 mm x 142 mm	75.00 g	1.00 dm ³
4058075152663	Shipping carton box 20	316 mm x 242 mm x 126 mm	1039.00 g	9.64 dm ³
4058075819450	Folding carton box 4	61 mm x 192 mm x 143 mm	144.00 g	1.67 dm ³
4058075819467	Shipping carton box 40	395 mm x 318 mm x 126 mm	1965.00 g	15.83 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.